


SWING-UP CENTER POST



CHOOSE YOUR OPTIONS

INSULATION	ThermoGuard™	EnergySaver™
Foam/Insulate	Polyurethane	Polystyrene
R-Value	26.0	17.1
U-Factor (Btu/hr/ft2/F)	0.114	0.145
Thickness	3 inches	3 inches
Exterior Steel	27 gauge <i>20 gauge upgrade, white only</i>	25 gauge <i>20 gauge upgrade, white only</i>
Interior Steel	27 gauge	25 gauge
Warranty* <i>Excludes Springs</i>	10 years	10 years

*For full warranty details contact your Midland dealer



COLORS



Color Select™

ColorSelect™ uses Sherwin Williams Polane® Solar Reflective Polyurethane Enamel, providing a durable, heat-repelling coating.

*Available in ThermoSteel™ only. **Available in ThermoGuard™ only. Due to the printing process, colors may vary.

WINDOWS



OPENING WIDTH

1-Post System: Max width 48 feet
2-Post System: Max width 60 feet

GLASS



*Tempered only. All other glass is available in both tempered and untempered.



MIDLAND™
GARAGE DOOR MFG CO

midlandgaragedoor.com • 800.437.4056

YOUR LOCAL GARAGE DOOR PROFESSIONAL